



SUPERTRAK, INC.®

26855 AIRPORT ROAD • PUNTA GORDA, FLORIDA 33982
PHONE: (941) 505-7800 • (800) 446-9858
FAX: (941) 505-2308 • www.supertrak.com

SK 400 • CUSTOM RUBBER TIRE MULCHER



SPECIFICATIONS

Base Unit:

- CAT® 533 Feller Buncher
- Rubber Tire

Engine:

- 400 Horsepower CAT® C12
- Fuel Capacity:
- 135 Gallons (511L)

Hydraulics:

- 135 Gallon (511L) Hydraulic Oil Tank
- Load Sensing Circuit
- Closed Loop Circuit
- Custom High Flow Package With 150gpm @5500psi

Pump Drive:

- 4 Pad Distribution Box

Cooling System:

- High Debris and High Ambient Temperature Radiator
- Cooling System With Auto Reversing Fan

Electrical:

- 24 Volt System (2 Batteries)

Controls:

- Pilot Operated Joystick System
- Foot Pedal

Safety Features:

- Front and Rear Halogen Work Lights
- Low Hydraulic Oil Shut Down System
- High Temperature Engine Shut Down System
- Backup Warning Alarm

Cab:

- Enclosed Cab With Air Conditioning and Heat
- Adjustable Seat
- Forestry Guard Package
- Lexan Front Windshield
- Windshield Wipers

Fecon Attachment Included:

- BH250-3 Bull Hog® Shredder/Mulcher Head
- Working Width of 88in (2235mm)
- Overall Width of 107in (2718mm)
- Operating Weight of 7000lbs (3175kg)
- Equipped With 48 Fixed Double Carbide Standard Tools

Overall Dimensions Including Fecon Attachment:

- Transport Length of 252in (6401mm)
- Transport Width of 124in (3150mm)
- Transport Height of 109in (2769mm)
- Approximate Weight of 42000lbs (19050kg)
- Approximate Turning Circle of 30ft (9.2m)