



# OS SUPERTRAK, INC.®

26855 AIRPORT ROAD • PUNTA GORDA, FLORIDA 33982  
PHONE: (941) 505-7800 • (800) 446-9858  
FAX: (941) 505-2308 • www.supertrak.com

## SK 400 TR • CUSTOM TRACK MULCHER



### SPECIFICATIONS

#### Base Unit:

- CAT® 953 Track Loader
- Steel Track

#### Engine:

- 400 Horsepower CAT® C12

#### Fuel Capacity:

- 110 Gallons (417L)

#### Hydraulics:

- 55 Gallon (208L) Hydraulic Oil Tank
- Pressure Compensated Load Sensing Circuit
- Custom High Flow Package With 150gpm @ 5500psi

#### Pump Drive:

- 4 Pad Distribution Box

#### Cooling System:

- High Debris and High Ambient Temperature Radiator
- Cooling System With Auto Reversing Fan

#### Electrical:

- 24 Volt System (2 Batteries)

#### Controls:

- Dual Axis Joystick Operated
- Microprocessor Controller for Thermostatic Control and Reversing of the Cooling Fan
- Straight Tracking
- Steering and Counter Rotate

#### Safety Features:

- Front and Rear Halogen Work Lights
- Low Hydraulic Oil Shut Down System
- Electronic Engine Management System
- Backup Warning Alarm

#### Cab:

- Enclosed Cab With Air Conditioning and Heat
- Adjustable Seat
- Lexan Front Windshield
- Windshield Wipers

#### Under Carriage:

- 32in (800mm) D5H Track Standard

- 102in (2590mm) On Ground Track Length

- 75in (1900mm) Track Gauge

#### Fecon Attachment Included:

- BH250-3 Bull Hog® Shredder/Mulcher Head
- Working Width of 88in (2235mm)
- Overall Width of 107in (2717mm)
- Operating Weight of 7000lbs (3175kg)
- Equipped With 48 Fixed Double Carbide Standard Tools

#### Overall Dimensions Including Fecon Attachment:

- Length of 293in (7442mm) (Not Including Oscillation Attachment)
- Width of 115in (2921mm)
- Height of 122in (3109mm)
- Approximate Weight of 52000lbs (23587kg)

#### Options:

- ± 10° Oscillation Attachment
- Cab Guards