



# SK170RR Excavator



## SK170RR Excavator

---

<b>Engine</b>	C4.4 Tier IV Final
<b>Engine Power</b>	129.5 kW (173.5hp)
<b>Weight</b>	18,234.4 kg 40,200lbs
<b>Std U/C</b>	46 shoe 20" Triple Grouser Polly Pad

# SK170RR Excavator

## Specifications

### Capacities:

Hydraulic 26 gallons  
Fuel 66 gallons  
DEF 19L DEF Tank 12V

### Hydraulic System:

Circuit Type Closed Loop  
High Flow 50 GPM @ 2200 RPM  
Max Pressure 5500 PSI

Std. Flow Aux 25 GPM @ 1900 RPM  
Std. Pressure 3500 PSI

### Dimensions:

Height 9'5"  
Width 102" (20" Grouser)

Length: 29.25"  
Tracks Options 20" Polly Pad  
Weight: 40,200lbs w/20" Grouser, Hy-Rail

Filtration: High Pressure Filters  
Remote Charge Filter  
Surge Protection  
1 Gallon Accumulator

Cooling: Heavy Duty Radiator / Oil Coolers  
Extra Large Intake Air  
Roof Louvers, Reversing Fans,  
Removable Debris Screens

Enclosure: Robust Engine/Service Doors

Controls: Std Cab layout with engine  
display and hydraulic diagnostics.



4 wheel Drive, 4 Wheel Brake Hy-Rail



26955 Airport Road  
Punta Gorda, Florida 33982  
1 800 446 9858  
1 941 505 7800  
[www.supertrak.com](http://www.supertrak.com)